

Quality Polymers



MANUFACTURED IN THE USA



30 Years of Innovation!

RANTEC CORPORATION

PO Box 729
Ranchester, WY 82839

Phone: (307) 655-9565

Fax: (307) 655-9528

www.ranteccorp.com

e-mail: rantec@ranteccorp.com

SPECTAC™

DISPERSIBLE POLYSACCHARIDE

PRODUCT DESCRIPTION

SPECTAC is an organic tackifier manufactured in the USA and is specifically designed for use as a hydraulically applied erosion control tackifier. **SPECTAC** is used as a stand alone temporary erosion control product or with wood, paper, or other native fiber mulches to provide superior bonding strength. **SPECTAC** is specifically designed to develop optimal slurry viscosity to improve sprayability and pump performance. **SPECTAC** disperses in water creating a lump free slurry, saving time and money.

APPLICATION GUIDELINES

It is recommended that **SPECTAC** be applied at 10 to 25 lbs per 1000 gallons of water depending on machine capacity. When used as an overspray for straw, use **SPECTAC** more concentrated at the rate of 40 lbs in 1000 gallons per acre with the use of 150 to 300 lbs of mulch as a marker.

GENERAL USEAGE RATES PER ACRE

SLOPE:	FLAT	4:1	3:1	2:1
LB/ACRE:	30-80	50-100	80-120	100-170

MIXING INSTRUCTIONS

1. Add water to tank to cover blades of lower agitator.
2. Add **SPECTAC** slowly while filling tank with agitator at high speed.
3. After **SPECTAC** is thoroughly mixed, add mulch seed, and fertilizer.

PACKAGING

SPECTAC is packaged in 50 lb bags, 40 bags per pallet with stretched wrapped cover and pallet liner.