

GUAR TACKIFIER ALTERNATIVES

Quality Polymers



MANUFACTURED IN THE USA



25 Years of Innovation!

RANTEC CORPORATION

PO Box 729
Ranchester, WY 82839

Phone: (307) 655-9565

Fax: (307) 655-9528

www.ranteccorp.com

e-mail: rantec@ranteccorp.com

HF5000 TACK™ HIGH PERFORMANCE TACKIFIER

PRODUCT DESCRIPTION

HF5000 Tack™ is an organic tackifier specially formulated to provide long-term strength and erosion control. **HF5000 Tack™** may be utilized with fiber or as a stand-alone over-spray or dust control.

APPLICATION GUIDELINES

HF5000 Tack™ may be prepared for application by mixing at 10 to 35-lb per 1000 gallons of water. Higher concentrations may be used with equipment capable of mixing and pumping higher viscosity. **HF5000 Tack™** reduces pumping friction and improves spray patterns due to its unique polymer properties.

GENERAL USAGE RATES PER ACRE

HF5000 Tack™

SLOPE:	FLAT	4:1	3:1	2:1	1:1
LB/ACRE:	15-40	40-60	60-80	80-120	120-220

PACKAGING

HF5000 Tack™ is packaged in 50-lb bags, 40 per pallet, stretch wrapped. Custom packages are available.